



Switchfuses

Switchgear Systems Ltd

16 Woodside Park, Rugby
Warwickshire, CV21 2NP

T 01788 577399

F 01788 577899

E mail@switchgear-systems.com

www.switchgear-systems.com

Sole UK distributor for



IP55 Enclosed Double Break Switchfuses

- 20A to 630A fully load rated
- Fitted with BS88 cartridge fuses
- Fuses isolated both sides

- 4 contact breaks per phase
- BSEN60947-3 conformity
- Door interlocked padlockable handles

I th AC22	Poles	Reference	Enclosure
160A	3 TP&N 4	ST-SILAD 16/3+F ST-SILAD 16/3+N+F ST-SILAD 16/4+F	500 x 400 x 200
200A	3 TP&N 4	ST-SILAD 20/3+F ST-SILAD 20/3+N+F ST-SILAD 20/4+F	500 x 400 x 200
250A	3 TP&N 4	ST-SILAD 20/3+F ST-SILAD 20/3+N+F ST-SILAD 20/4+F	500 x 400 x 200
315A	3 TP&N 4	ST-SILAD 20/3+F ST-SILAD 20/3+N+F ST-SILAD 20/4+F	500 x 400 x 200

I th AC22	Poles	Reference	Enclosure
400A	3 TP&N 4	ST-SILAD 40/3+F ST-SILAD 40/3+N+F ST-SILAD 40/4+F	600 x 400 x 260
500A	3 TP&N 4	ST-SILAD 50/3+F ST-SILAD 50/3+N+F ST-SILAD 50/4+F	800 x 600 x 320
630A	3 TP&N 4	ST-SILAD 63/3+F ST-SILAD 63/3+N+F ST-SILAD 63/4+F	800 x 600 x 320

Enclosed switchfuses from 20A to 125A fitted in IP41 steel enclosures are available as standard in the Pro-Line range.

Switches can also be supplied in IP65, Stainless Steel and GRP enclosures, in sizes to suit customer preference.



Panel Mounting Double Break Switchfuses

- 20A to 630A available fully load rated
- 3, 3+N, 4 pole available
- Fuses isolated both sides

- 4 contact breaks per phase
- BSEN60947-3 conformity
- Door interlocked padlockable handles

I th AC22	Poles	Reference
20A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4
32A	3 TP&N 4	SILAD 3/3 SILAD 3/3+N SILAD 3/4
63A	3 TP&N 4	SILAD 6/3 SILAD 6/3+N SILAD 6/4
100A	3 TP&N 4	SILAD 10/3 SILAD 10/3+N SILAD 10/4

I th AC22	Poles	Reference
125A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4
160A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4
200A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4
250A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4

I th AC22	Poles	Reference
315A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4
400A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4
500A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4
630A	3 TP&N 4	SILAD 2/3 SILAD 2/3+N SILAD 2/4

Rating	Terminal shroud	Ext shaft	Aux
20, 32A	Not required	190501	191429
63, 100A	19135001	190501	191420
125 to 315A	191351	190502	191433

Rating	Terminal shroud	Ext shaft	Aux
400A	19135301 top 19135302 bottom	19060302	191436
500, 630A	19135401 top 19135402 bottom	19060302	191436